



AN ISO 9001:2008 CERTIFIED COMPANY













OUR PRODUCTS:-

- ONLOAD CHANGEOVER
- LOAD BREAK SWITCH
- ONLOAD BYPASS SWITCH
- OFFLOAD CHANGEOVER SWITCH
- SWITCH DISCONNECTOR FUSE

- MAIN SWITCH REWIRABLE
- HRC DOUBLE BREAK SWITCH
- BUSBAR
- HRC FUSE BASE
- METAL CLAD PLUG & SOCKETS



ONLOAD CHANGEOVER SWITCH

- Range From 63 Amp to 1000 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Ensures High Mechanical & Electrical Strength
- Compact Model
- Available in Open Execution & Sheet Steel Enclosure

ONLOAD ISOLATOR / LOAD BREAK SWITCH

- Range from 63 Amp to 1000 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Ensures High Mechanical & Electrical Strength
- Compact Model
- 80KA Breaking Capacity
- Available in Open Execution & Sheet Steel Enclosure

ONLOAD BYPASS SWITCH

- Range from 63 Amp to 1000 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Ensures High Mechanical & Electrical Strength
- Compact Model
- 80KA Breaking Capacity
- Available in Open Execution & Sheet Steel Enclosure









SWITCH DISCONNECTOR FUSE

- Range From 32 Amp to 630 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Ensures High Mechanical & Electrical Strength
- Compact Model
- Fully insulated DMC Body
- Available in Open Execution & Sheet Steel Enclosure

OFFLOAD CHANGEOVER SWITCH

- Range from 63 Amp to 1000 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Comes With Door Interlock Feature
- Enclosure is made up of CRC Sheet

MAIN SWITCH REWIRABLE

- Range from 32 Amp to 200 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Comes With Door Interlock Feature
- Enclosure is made up of CRC Sheet

HRC DOUBLE BREAK SWITCH

- Range from 63 Amp to 1000 Amp
- Conforms to IS/IEC:60947-3
- Quick Make & Break Mechanism
- Comes With Door Interlock Feature
- Enclosure is made up of CRC Sheet











BUSBAR

- Range From 32 Amp to 630 Amp
- Fitted with Superior Silver Plated Copper Strips
- Heavy Duty material ensures High Strength
- Flame Proof Insulation
- Protection Category IP23

HRC FUSE BASE

- Range from 32 Amp to 630 Amp
- Conforms to IS:13703 & IEC:269
- Rated Voltage 500V, 50Hz Ac
- 80KA Breaking Capacity
- Low Watt Loss

METAL CLAD PLUG & SOCKETS

• Single Phase : 20 AMP (2P+E) 220V

• Three Phase: 20 AMP, 30 AMP (3P+E+N) 440V

- Outer Casing made of non corrosive die cast Aluminium Alloy
- Interior moulded of Superior Grade Phenolic
 / Polyester Compund
- Heavy Duty Brass Pin







OUR BRANDS:-





Mfd. By:

DASHMESH SWITCHGEAR

INDIA

Contact :- +91-9811030172, +91-9999892973, Tel: +91-120-2988969

Email: electraswitchgears@gmail.com